


<b>ENGINEERING SHEET</b>	TITLE <b>HITACHI FUSE FREE BREAKER</b>	CODE	WORK CODE
--------------------------	---	------	-----------

Ampere Frame (AF)		3200		
Type		F-3200EB		
Number of Poles		3		
Rate Current (A) (Base Ambient Temperature 40°C)		1600/2000/2500/ 2800/3200 Adjustable		
Rate Insulation Voltage Ui (V)		690		
Rate Impulse Withstand Voltage Uimp (kV)		8		
Rate Breaking Capacity (kA)	IEC 60947-2 (Icu/Ics)	AC690V	45/42	
		AC440V	85/65	
		AC415V	85/65	
		AC400V	100/75	
		AC380V	100/75	
		AC240V	125/94	
		AC230V	125/94	
		DC250V	-	
DC125V	-			
Dimension (mm)		a	320	
		b	450	
		c	185	
		d	245	
Net Weight (kg)		65		
Automatic Tripping Device		Electronic		
Interior Accessories	Alarm Switch (AL)	AL-1C	○	
		AL-2C	○	
	Auxiliary Switch (AUX)	AUX-1C	○	
		AUX-2C	○	
	Alarm Switch (AL) + Auxiliary Switch (AUX)	AL-1C- AUX-1C	○	
		AL-1C- AUX-2C	○	
		AL-2C- AUX-2C	-	
	Shunt Trip (SHT)		○	
Undervoltage Trip (UVT)		○		
Terminal Block (TB)		○		
Exterior Accessories	Rear-Connecting Stud	(STB)	-	
		(BSD)	○	
	Flush Mounting Base Assembly (GKW-STB)		-	
	Flush Mounting Base Assembly (GK- GKW-BSD)		○ (GK)	
	Drawout Assembly (PDK)		-	
	Plug-in Mounting Base Assembly (PK)		-	
	Mechanical Interlock (MIW)		○	
	Motor-Operating Mechanism (MMK)		○	
	Lock Cover (LC)		-	
	Handle Lock (HL)		○	
	Handle Operating Mechanism	HA	○	
		HM	-	
	Terminal Cover (TMC)	Front type	Std.	-
			Short	-
		Rear type	Long	-
		Long	-	
		BTC	-	
IEC Rial 35 mm.		-		
Trip Button		●		
Phase Separator		●		

**Note :**

- = Option
- = Standard

Reference : DWG JP No. 43076860.

SYM.	REVISION	DATE	REVD.	CHKD.	APPD.
DWN.	O.SITTICHAJ	15/6/2020			
CHKD.	Ch.Chonticha	15/6/2020			
	M.Somkiat				
APPD.	S.Sugai	15/6/2020			

<b>HITACHI</b>		HITT WORK DWG. NO.	SH.	REV
Hitachi Industrial Technology (Thailand), Ltd.		<b>4HTN001235</b>	1	00